



DAMTITE WATERPROOFING

733 E. Main Street
 Monongahela, PA 15063-1499
 1-800-333-4333 • 1-724-258-7175 • Fax: 724-258-3188
 e-mail: info@damtitewaterproofing.com
 website: www.damtitewaterproofing.com



**Latex Base, Ready Mixed
 Masonry Waterproofer**

White - Gallon and 5 Gallon

FOR CONCRETE, BRICK & MASONRY

- **10-Year Waterproofing Guarantee**
- **Withstands 55 ft (16,7 m) Wall of Water**
- **Low Odor; Easy Clean-up**
- **Reduces Radon Gas Penetration**

EXCELLENT FOR:

- **Concrete/Cinder Block, Poured Concrete, Masonry, Stucco & Brick**
- **Interior/Exterior, Above/Below Grade**
- **Basement & Garage Walls**
- **Retaining & Sea Walls**
- **Bird Baths, Fountains, Fish Ponds and Planters**
- **Bare Concrete Swimming Pools**
- **Unventilated Crawl Spaces and Cellar Walls**
- **Exterior Above-Grade Foundations**
- **Reducing Radon Gas Penetration**

Description:

Damtite Latex Waterproofer is a low-odor, high performance masonry waterproofer with a bright white finish. Ideal for interior & exterior, above & below grade applications. This durable, alkali-resistant coating provides excellent waterproofing protection with a slightly textured, decorative finish for all masonry, cinder & concrete block, poured concrete, brick, stone, stucco, basement, garage and retaining walls & foundations. No pre-mixing or pre-wetting is needed. Stops over 25 psi of hydrostatic water pressure. Fast drying with easy soap & water cleanup. Tests Passed: ASTM D-7088 Resistance to Hydrostatic Pressure & ASTM D-6904 Resistance to Wind Driven Rain.

Note: Not for use on floors or horizontal surfaces. Will not withstand foot traffic. May be applied over previously-painted surface in sound condition but the warranty is void, since *Damtite* must enter pores to perform.

Surface Preparation:

Provides best results applied to dry surfaces when no rain expected for several days, but surface can be slightly damp. Clean the surface thoroughly, removing any loose mortar, paint, dirt, dust, grease, oil, form-release agents or algae. Follow Damtite's Step 1-2-3 Project Guide, including: **Step 1 - Prepare the Surface:** Remove any powdery, salt-like deposits (efflorescence) or neutralize alkali with *Damtite Concrete Cleaner*. Rinse thoroughly. **Step 2 - Repair the Surface:** Patch cracks or holes in the mortar joints, wall-floor joints, or in the concrete block with *Damtite Waterproof Hydraulic Cement*. **Step 3 - Decorate & Waterproof:** Apply two coats of *Damtite*.

Application:

STIR THOROUGHLY BEFORE & DURING USE. DO NOT THIN. Only apply when air and surface temperature are 50°F (10°C) or higher and expected for 48 hours. Apply directly from the pail onto dry/slightly damp, bare masonry. Apply a generous first coat, using a good quality nylon-bristle brush or ¾ inch nap roller. Work the first coat in different directions to insure filling all pores, pinholes and voids. Allow the first coat to dry 12-24 hours before applying second coat. Two coats are required for warranty & best performance. For severe seepage areas, an additional coat may be required to fill pin holes and pores. Inspect surface after second coat is applied. When used on insides of planters, fish ponds, concrete water-holding tanks or unventilated areas, allow to dry minimum 1 week before filling.

Coverage:

On rough, porous surfaces, expect 75-100 sq. ft. (7-9,3 m²); on smooth concrete or previously painted areas, up to 125 sq. ft. (11,6 m²).

Tinting:

May be tinted to light shades with alkali-proof universal tinting colors. Use only 50% of color normally recommended; not more than 2 fl. oz. of colorant per gallon.

Drying Time:

Dry to touch in 2 hours normally. Allow 12-24 hours before next coat applied.

Clean-Up/Storage/Disposal:

Clean hands and tools immediately after use with soap and warm water. Store above 40°F (4.5°C). Dispose of product in accordance with local, state and federal regulations.

Important:

Damtite Powder Waterproofer is recommended for coating ponds or water-holding projects, such as concrete cisterns, fish ponds, or water tanks. Do not apply to frost covered or frozen walls, or in areas where surface temperature is expected to fall below 40°F (4.5°C) within 48 hours after application. Do not use on floors, sandstone or glazed surface. Product will not withstand foot traffic.

LIMITED WARRANTY:

Damtite Latex Waterproofer, when applied in accordance with directions on this label, on a properly prepared BARE masonry surface, is warranted to provide a waterproof coating for ten (10) years from date of sale or we will refund the purchase price of this product, upon presentation of purchase receipt. This is the exclusive remedy. Product failure due to incorrect product application or surface preparation, surface cracking, swimming pools application, recurring efflorescence, structural damage or use over previously painted areas are excluded. This warranty excludes labor or the cost of labor for application nor any other damages.

CAUTION

**KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY.**

Use only with adequate ventilation. Vapors Harmful. May affect the brain or nervous system, causing dizziness, headaches or nausea. May cause eye, nose, throat or skin irritation. Harmful if swallowed. May be harmful if absorbed through skin. Avoid breathing vapors and mist. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying time. If experience headaches, eye watering, nausea, or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, move to a fresh air location and wear a properly-fitted NIOSH-approved respirator, during and after application. Follow respirator manufacturer's directions for use. Do not get product in eyes, on skin or clothing. Wash thoroughly after handling. Close lid after use. **FIRST AID:** For eye contact: Flush eyes thoroughly with water for at least 15 minutes. Get medical attention immediately. Inhalation: if experience difficulty breathing, move to area with fresh air. If difficulty continues, seek medical attention immediately. Ingestion: Drink two glasses of water, do not induce vomiting. Get immediate medical attention. If Spilled: contain spilled material and remove with absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Size	Color	Stock No.	Pack
Gallon	White	03550	4
5 Gallon	White	03555	1