



DAMTITE WATERPROOFING
 733 E. Main Street
 Monongahela, PA 15063-1499
 1-724-258-7175 • Fax: 724-258-3188
 e-mail: info@damtitewaterproofing.com
 website: www.damtitewaterproofing.com

Powder Waterproofer

Supertite

White - 35 lb. Pail

**SELF BONDING
 FOR CONCRETE, BRICK & MASONRY**



- **10-Year Guarantee**
- **Economical, just add Water & Mix**
- **Adheres to All Types of Masonry**
- **Safe for Drinking Water Tanks and Cisterns**

EXCELLENT FOR:

- **Concrete Block, Cinder Block, Poured Concrete, Fieldstone, Masonry, Brick & Stucco**
- **Interior/Exterior, Above/Below Grade**
- **Concrete Drinking Water Tanks & Cisterns**
- **Basement & Garage Walls**
- **Retaining & Sea Walls**
- **Bird baths, Fountains, Fish Ponds, Planters & Bare Concrete Swimming Pools**
- **Foundations – Above & Below Grade**
- **Unventilated Crawl Spaces & Cellars**
- **Concrete Silos & Tornado Shelters**
- **Reducing Radon Gas Penetration**

Description:

Heavy-Duty, Portland cement-based waterproofing coating with dry polymer-modified additive for best adhesion. Eliminates need for liquid bonding additive to mix for non-porous, smooth surfaces. Ideal for sealing, protecting & decorating vertical walls and surfaces constructed of concrete, masonry, stone, brick or stucco. Easy to use; just add to water. Eliminates dampness; resists mold/mildew & flaking or chalking while beautifying and sealing all pores & voids. Formulated for application directly onto damp or wet surfaces.

Available sizes and coverages :
 35 lb. pail - covers up to 260 sq. ft.

Size	Color	Stock No.	Pack
35 lb. Pail	White	01351	1

Breathable coating while withstanding 22 psi of hydrostatic pressure. Also, it reduces Radon Gas infiltration. Not formulated to withstand foot traffic.
Tip: Wear protective gloves and goggles.

Surface Preparation:

Most important step for best waterproofing results and adhesion. Clean the surface thoroughly with wire brush to remove any loose mortar, paint, dust, grease or oil. Then, follow our Step 1-2-3 Product Guidelines. Step 1-Prepare the Surface: Remove powdery, salt-like deposit (efflorescence) or form-oil residue with **Damtite Concrete Cleaner**. After 20-30 minutes, rinse surface well with water. Step 2-Repair the Surface: Fill holes, cracks or active water leaks and mortar joints with **Damtite Waterproofing Hydraulic Cement**. Step 3-Decorate & Waterproof: apply 2 coats of this product. Important: using garden sprayer, hose set to fine mist or brush, completely dampen surface with clean water immediately prior to applying and keep surface wet during application.

WARNING! If you scrape, sand, or remove paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Mixing:

Since the mix will harden in 1 hour, mix in a clean container, mix not more than 1/2 of the powder or 17 1/2 lb (7,9 kg) - measured as 6.5 quarts (7,2 L) of powder. For porous bare surfaces, first add 2 1/2 quarts (2,37 L) of clean water into the container. Then gradually add 17 1/2 lb (7,9 kg) of powder while stirring constantly with paint stirrer or attachment to electric drill to a "pancake batter" consistency. Allow mix to set undisturbed for 15 minutes to activate the waterproofing agents before applying mix. During application, stir often. To prevent hardening, add a little extra water if needed. *For smaller quantity mixes, add 2.5 parts powder to 1 part clean water.*

Application:

TWO-COATS REQUIRED FOR BEST RESULTS & WARRANTY. For smaller projects, use a 4-row masonry brush to apply product; for larger projects, spray using plaster's hopper spray gun. Insure surface is uniformly pre-wetted & dampened with clean water before applying each coat! Start at top of wall in corner and work down wall, applying liberal amount of product, brushing first coat in different directions to penetrate & fill pores, pinholes

and hairline cracks. Smooth out the second coat by lightly brushing in one direction across wall. To avoid lap marks, complete from corner to corner in one application. Dip brush in clean water often for easier workability. Allow first coat to dry 24-48 hours (or longer in unventilated and/or severe leaking areas). Dampen surface lightly with clean water prior to applying second coat. Follow same procedures to apply second coat. Textured or swirled finishes possible. For bottom 1/3rd of basement walls with persistent water seepage problems, apply a thicker second or third coat.

Limitations:

- Do not apply to frosted surfaces or when surface temperature is below 50°F (10°C) within 48-72 hours.
- If applying to exterior surfaces during high winds, direct hot sun or high temperatures, each coat must be fog sprayed with fine, low pressure mist of clean water 2-3 times/day to prevent drying too quickly, which will cause cracking.
- May not performance well over previously painted surfaces, field/sandstone, or glazed tile/brick, so first apply small sample test area.

Coverage:

Surfaces Smooth/Non-Porous or 2nd Coat: Up to 260 sq ft (24,2 m²). Rough/Porous or 1st Coat: 200 sq ft (18,6 m²).

Clean-Up/Storage/Disposal:

Wash hands & tools with soap & water immediately after use. Store unused powder tightly sealed in original container. Dispose of hardened product in accordance with local, state & federal requirements.

CAUTION:

KEEP OUT OF REACH OF CHILDREN.

Contains Portland cement, silica & lime. May cause skin burns and/or allergic reactions or be irritating to eyes & skin. Wear protective gloves & goggles. For prolonged professional use, avoid breathing dust by wearing NIOSH/MSHS-approved respirator & by mixing in area with adequate ventilation. In case of eye contact, flush eyes with clean water immediately and call doctor or poison center. **DO NOT TAKE INTERNALLY.** If ingested, take 1-2 glasses of water & call doctor immediately.

WARNING: This product contains crystalline silica, a chemical known to State of California Proposition 65 to cause cancer. Risk of cancer is based upon breathing of silica dust particles with prolonged occupational usage over many years.